



ITERATIVE DEVELOPMENT SUMMARY – 1000 PSI CLASS

This document summarizes the iterative development process undertaken to achieve the final qualified operating rating of 1000 psi differential pressure at 575°F for the Hybrid Swellable Packer and Thermal Expansion Sub system. The graph below illustrates progressive design improvements across multiple development iterations.




Each iteration reflects controlled optimization of elastomer formulation, metal geometry, and load transfer mechanisms, resulting in stable and repeatable performance at elevated temperature and pressure conditions.


SUMA JEOTEKNİK İNŞAAT
 TUR.İTH.İHR. TIC. VE SAN. LTD.ŞTİ
 İnşaat Dr. Suat Sümer (Jeoteknik)
 Dış Geoteknik (Registration) No: 2328705C
 Aslanbey V.D. 782 022 7957
 Hasancıklı Mah. 89016 Sok. No: 20/U
 Onikişubat/KAHRAMANMARAŞ

PERFORMANCE ENVELOPE – 1000 PSI CLASS


1. Differential Pressure vs Temperature

Qualified Differential Pressure vs Temperature (1000 psi Class)



SUMA JEOTEKNİK İNŞAAT
TUR.İTH.İHR.TİC.VEL.SAN.LTD.ŞTİ
İnşaat Dr. Suat ŞİRİN (Jeoteknik)
Jip Jeoteknik (Registration) No: 2328105C
Aslanbey V.D. 762 072 7957
Hasancıklı Mah. 89016 Sk.No.20/U
Onikişubat/KAHRAMANMARAŞ

2. Swell Capacity vs Time



3. Thermal Expansion Stroke vs Temperature

